

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 01/08/2008

Reviewed on 01/19/2007

1 Identification of substance:

Product details:

Product name: Isobutylamine

Stock number:

A11017

L14469

Manufacturer/Supplier:

Alfa Aesar, A Johnson Matthey Company
Johnson Matthey Catalog Company, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Emergency Phone: (978) 521-6300

CHEMTREC: (800) 424-9300

Web Site: www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency information:

During normal hours the Health, Safety and Environmental Department.

After normal hours call Chemtrec at (800) 424-9300.

2 Composition/Data on components:

Chemical characterization:

Description: (CAS#)

Isobutylamine (CAS# 78-81-9): 100%

Identification number(s):

EINECS Number: 201-145-4

3 Hazards identification

Hazard description:



C Corrosive

F Highly flammable

Information pertaining to particular dangers for man and environment

R 11 Highly flammable.

R 22 Harmful if swallowed.

R 34 Causes burns.

Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH	2
FIRE	3
REACTIVITY	1

Health (acute effects) = 2

Flammability = 3

Reactivity = 1

4 First aid measures

General information

Immediately remove any clothing soiled by the product.

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

(Contd. on page 2)

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 01/08/2008

Reviewed on 01/19/2007

Product name: Isobutylamine

(Contd. of page 1)

After skin contact

Immediately wash with water and soap and rinse thoroughly.
Seek immediate medical advice.

After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing Seek immediate medical advice.

5 Fire fighting measures**Suitable extinguishing agents**

In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.

For safety reasons unsuitable extinguishing agents Water

Special hazards caused by the material, its products of combustion or resulting gases:

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

6 Accidental release measures**Person-related safety precautions:**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Measures for environmental protection:

Do not allow material to be released to the environment without proper governmental permits.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Keep away from ignition sources.

Additional information:

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage**Handling****Information for safe handling:**

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away.

Protect against electrostatic charges.

(Contd. on page 3)

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 01/08/2008

Reviewed on 01/19/2007

Product name: Isobutylamine

(Contd. of page 2)

Fumes can combine with air to form an explosive mixture.

Storage**Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

8 Exposure controls and personal protection**Additional information about design of technical systems:**

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Components with limit values that require monitoring at the workplace:

Isobutylamine

	ppm
Austria MAK	5 (skin)
Denmark TWA	5 (skin)
Germany MAK	5 (skin)
Switzerland MAK-W	5; 25-STEL

Components with limit values that require monitoring at the workplace:**Additional information:** No data**Personal protective equipment****General protective and hygienic measures**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

Use suitable respirator when high concentrations are present.

Protection of hands:

Impervious gloves

Check protective gloves prior to each use for their proper condition.

Material of gloves

The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Eye protection:

Safety glasses

Tightly sealed goggles

Full face protection

Body protection: Protective work clothing.**9 Physical and chemical properties:****General Information**

Form:	Liquid
Color:	Colorless

(Contd. on page 4)

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 01/08/2008

Reviewed on 01/19/2007

Product name: Isobutylamine

(Contd. of page 3)

Odor:	Not determined
Change in condition	
Melting point/Melting range:	Not determined
Boiling point/Boiling range:	64-71°C (147-160°F)
Sublimation temperature / start:	Not determined
Flash point:	-21°C (-6°F)
Ignition temperature:	Not determined
Decomposition temperature:	Not determined
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures is possible.
Explosion limits:	
Lower:	Not determined
Upper:	Not determined
Vapor pressure:	Not determined
Density at 20°C (68°F):	0.736 g/cm ³

10 Stability and reactivity**Thermal decomposition / conditions to be avoided:**

Decomposition will not occur if used and stored according to specifications.

Materials to be avoided: Oxidizing agents

Dangerous reactions No dangerous reactions known

Dangerous products of decomposition:

Carbon monoxide and carbon dioxide

Nitrogen oxides

11 Toxicological information**Acute toxicity:****LD/LC50 values that are relevant for classification:**

Oral	LD50	224 mg/kg (rat)
------	------	-----------------

Primary irritant effect:**on the skin:**

Corrosive effect on skin and mucous membranes.

Irritant to skin and mucous membranes.

on the eye:

Strong corrosive effect.

Irritating effect.

Sensitization: No sensitizing effects known.

Subacute to chronic toxicity:

Corrosive materials are acutely destructive to the respiratory tract, eyes, skin and digestive tract. Eye contact may result in permanent damage and complete vision loss. Inhalation may result in respiratory effects such as inflammation, edema, and chemical pneumonitis. May cause coughing, wheezing, laryngitis, shortness of breath, headache, nausea and vomiting. Ingestion may cause damage to the mouth, throat and esophagus.

May cause skin burns or irritation depending on the severity of the exposure.

(Contd. on page 5)

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 01/08/2008

Reviewed on 01/19/2007

Product name: Isobutylamine

(Contd. of page 4)

Additional toxicological information:

Swallowing will lead to a strong corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

12 Ecological information:**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Do not allow material to be released to the environment without proper governmental permits.

13 Disposal considerations**Product:****Recommendation**

Consult state, local or national regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information**DOT regulations:**

Hazard class:	3
Identification number:	UN1214
Packing group:	II
Proper shipping name (technical name):	ISOBUTYLAMINE
Label	3+8

Land transport ADR/RID (cross-border)

ADR/RID class:	3 (FC) Flammable liquids
Danger code (Kemler):	338
UN-Number:	1214
Packaging group:	II
Description of goods:	1214 ISOBUTYLAMINE

(Contd. on page 6)

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 01/08/2008

Reviewed on 01/19/2007

Product name: Isobutylamine

(Contd. of page 5)

Maritime transport IMDG:

IMDG Class: 3
UN Number: 1214
Label 3+8
Packaging group: II
Proper shipping name: ISOBUTYLAMINE

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: 3
UN/ID Number: 1214
Label 3+8
Packaging group: II
Proper shipping name: ISOBUTYLAMINE

15 Regulations**Product related hazard informations:****Hazard symbols:**

C Corrosive
 F Highly flammable

Risk phrases:

11 Highly flammable.
 22 Harmful if swallowed.
 34 Causes burns.

Safety phrases:

7 Keep container tightly closed.
 20 When using do not eat or drink.
 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 33 Take precautionary measures against static discharges.
 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
 45 In case of accident or if you feel unwell, seek medical advice immediately.
 60 This material and its container must be disposed of as hazardous waste.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

Information about limitation of use:

For use only by technically qualified individuals.
 This product is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

USA

(Contd. on page 7)

Material Safety Data Sheet
acc. to OSHA and ANSI

Printing date 01/08/2008

Reviewed on 01/19/2007

Product name: Isobutylamine

(Contd. of page 6)

16 Other information:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing MSDS: Health, Safety and Environmental Department.

Contact: Paul V. Connolly

USA