

MSDS Number: **M8012** * * * * * *Effective Date: 08/18/05* * * * * * *Supersedes: 08/10/04*

MSDS **Material Safety Data Sheet**

From: Mallinckrodt Baker, Inc.
222 Red School Lane
Phillipsburg, NJ 08865



Mallinckrodt
CHEMICALS



24 Hour Emergency Telephone: 908-859-2151
CHEMTREC: 1-800-424-9300

National Response in Canada
CANUTEC: 613-996-6666

Outside U.S. and Canada
Chemtrec: 703-527-3887

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

All non-emergency questions should be directed to Customer Service (1-800-582-2537) for assistance.

2-AMINOETHANOL

1. Product Identification

Synonyms: Monoethanolamine; Ethanolamine; beta-Aminoethanol, ethylolamine; glycinol

CAS No.: 141-43-5

Molecular Weight: 61.08

Chemical Formula: NH₂CH₂CH₂OH

Product Codes:

J.T. Baker: 6200, 9314, 9339

Mallinckrodt: 6339

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent
Hazardous	-----	-----
-----	-----	-----
Ethanolamine	141-43-5	99 - 100%
Yes		

3. Hazards Identification

Emergency Overview

DANGER! CAUSES BURNS. COMBUSTIBLE. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. AFFECTS CENTRAL NERVOUS SYSTEM.

SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 3 - Severe

Flammability Rating: 2 - Moderate

Reactivity Rating: 2 - Moderate

Contact Rating: 4 - Extreme (Corrosive)

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD;
PROPER GLOVES; CLASS B EXTINGUISHER

Storage Color Code: White (Corrosive)

Potential Health Effects

Inhalation:

Vapor may cause irritation to the respiratory tract. Symptoms may include sore throat, coughing, respiratory distress, headache, lethargy, and narcosis. Exposure to higher concentrations may cause pulmonary irritation, and kidney and liver damage.

Ingestion:

May cause mucosal burns of the mouth and esophagus, abdominal pain, nausea, and vomiting. May cause systemic poisoning with symptoms paralleling inhalation.

Skin Contact:

May cause irritation, redness, burns, and pain. May be absorbed through the skin; symptoms may parallel inhalation.

Eye Contact:

Vapors and contact may cause severe irritation, burns, redness, pain, and blurred vision.

Chronic Exposure:

Prolonged or repeated skin exposure may cause severe irritation or dermatitis.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or impaired liver, kidney, and pulmonary function may be more susceptible to the effects of this material.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion:

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician immediately.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Flash point: 85C (185F) CC

Autoignition temperature: 410C (770F)

Flammable limits in air % by volume:

lel: 5.5; uel: 17

Combustible.

Explosion:

Above flash point, vapor-air mixtures are explosive within flammable limits noted above.

Fire Extinguishing Media:

Water spray, dry chemical, alcohol foam, or carbon dioxide. Water spray may be used to keep fire exposed containers cool. Water may be used to flush spills away from exposures and to dilute spills to non-flammable mixtures.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer!

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from any source of heat or ignition. Isolate from oxidizing materials. Avoid contact with copper and copper alloys. Material is suitably handled in stainless steel equipment. Do not use aluminum for storage of aqueous solutions. Outside or detached storage is preferred. Isolate from acidic materials. Monoethanolamine is generally stored in plain steel equipment. Product may solidify at room temperature. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

2-Aminoethanol:

-ACGIH Threshold Limit Value (TLV):

3 ppm (TWA) 6 ppm (STEL)

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a full facepiece respirator with organic vapor cartridge may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Clear, colorless liquid.

Odor:

Ammonia odor.

Solubility:

Miscible in water.

Density:

1.02

pH:

12.1 (25% solution)

% Volatiles by volume @ 21C (70F):

0

Boiling Point:

170C (338F)

Melting Point:

10C (50F)

Vapor Density (Air=1):

2.10

Vapor Pressure (mm Hg):

0.4 @ 20C (68F)

Evaporation Rate (BuAc=1):

< 1

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage. Hygroscopic. Absorbs carbon dioxide. A strong base.

Hazardous Decomposition Products:

Burning may produce carbon monoxide, carbon dioxide, nitrogen oxides.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Sulfuric acid, hydrochloric acid, acetic acid, carbon dioxide in the air, copper, copper alloys, galvanized iron, aluminum, acetic anhydride, acrolein, acrylic acid, acrylonitrile, chlorosulfonic acid, epichlorohydrin, hydrofluoric acid, mesityl oxide, nitric acid, oleum, beta-propiolactone, and vinyl acetate.

Conditions to Avoid:

Heat, flame, other sources of ignition.

11. Toxicological Information

Oral rat LD50: 1720 mg/kg; Inhalation mouse LC50: 2420 mg/m³/2hr; Skin rabbit LD50:

1000 mg/kg Irritation data: Skin rabbit - 505 mg moderate; Eye rabbit - 0.250 mg severe. Investigated as a mutagen and reproductive effector.

-----\Cancer Lists\-----

Ingredient Category	---NTP Carcinogen---		IARC
	Known	Anticipated	
Ethanolamine (141-43-5) None	No	No	

12. Ecological Information

Environmental Fate:

When released into the soil, this material may biodegrade to a moderate extent. When released into the soil, this material may leach into groundwater. When released into water, this material may biodegrade to a moderate extent. This material has an estimated bioconcentration factor (BCF) of less than 100. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life of less than 1 day. When released into the air, this material may be removed from the atmosphere to a moderate extent by wet deposition.

Environmental Toxicity:

No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: ETHANOLAMINE

Hazard Class: 8

UN/NA: UN2491
Packing Group: III
Information reported for product/size: 465LB

International (Water, I.M.O.)

Proper Shipping Name: ETHANOLAMINE
Hazard Class: 8
UN/NA: UN2491
Packing Group: III
Information reported for product/size: 465LB

International (Air, I.C.A.O.)

Proper Shipping Name: ETHANOLAMINE
Hazard Class: 8
UN/NA: UN2491
Packing Group: III
Information reported for product/size: 465LB

15. Regulatory Information

-----\Chemical Inventory Status - Part 1\-----

Ingredient TSCA EC Japan
Australia

Ethanolamine (141-43-5) Yes Yes Yes
Yes

-----\Chemical Inventory Status - Part 2\-----

Ingredient Korea --Canada--
Phil. DSL NDSL

Ethanolamine (141-43-5) Yes Yes No
Yes

-----\Federal, State & International Regulations - Part 1\-----

313----- -SARA 302- -----SARA
Ingredient RQ TPQ List
Chemical Catg.

Ethanolamine (141-43-5)	No	No	No
No			
-----\Federal, State & International Regulations - Part 2\-----			
			-RCRA-
TSCA-			-
Ingredient	CERCLA	261.33	8 (d)

-			
Ethanolamine (141-43-5)	No	No	No

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No
SARA 311/312: Acute: Yes Chronic: No Fire: Yes Pressure: No
Reactivity: No (Pure / Liquid)

Australian Hazchem Code: 2R
Poison Schedule: None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: **3** Flammability: **2** Reactivity: **0**

Label Hazard Warning:

DANGER! CAUSES BURNS. COMBUSTIBLE. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. AFFECTS CENTRAL NERVOUS SYSTEM.

Label Precautions:

- Do not get in eyes, on skin, or on clothing.
- Do not breathe vapor.
- Keep container closed.
- Use with adequate ventilation.
- Wash thoroughly after handling.
- Keep away from heat and flame.

Label First Aid:

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases call a physician.

Product Use:

Laboratory Reagent.

Revision Information:

MSDS Section(s) changed since last revision of document include: 3.

Disclaimer:

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by: Environmental Health & Safety
Phone Number: (314) 654-1600 (U.S.A.)